SECTION 101467 TACTILE SIGNAGE

PART 1 - GENERAL

1.1 SECTION INCLUDES

A. Room Name/Number Signs.
B. Directional Signs.
C. Gender Appropriate Restroom Signs.
D. Fire Exit Signs.

1.2 REFERENCES

A. ADAAG - Americans with Disabilities Act Accessibility Guidelines; U.S. Architectural and Transportation Barriers Compliance Board.
B. ANSI A117.1 - Specifications for Making Buildings and Facilities Accessible to and Usable by Physically Handicapped People.
C. Americans with Disabilities Act (ADA).
D. Architectural Barriers Texas Accessibility Standards (TAS).

1.3 ALLOWANCES

A. Provide eight (8) room name/number signs for interior space/doors.
B. Provide two (2) directional signs.
C. Provide two (2) gender appropriate restroom signs.
D. Provide three (3) fire exit signs.

1.4 SUBMITTALS

A. Submit under provisions of Section 01 33 00.
B. Product Data and installation instructions for each type of sign specified.
C. Shop Drawings:
   1. Show layout, signage copy, size and type of mounting for each sign.
   2. Indicate location of each individual sign in the project.
D. Selection Samples: Sample of two for each sign with full range of color, pattern, and surface texture available.
E. Verification Samples: Sample of two for each sign type for verification of quality, color, pattern, and surface texture.

1.5 QUALITY ASSURANCE

A. Manufacturer Qualification:
   1. Specializing in the products specified with minimum five years' experience.
   2. Single source responsibility: Obtain signs from one source and a single manufacturer.
B. Regulatory Requirements: Conform to applicable codes, ADAAG and ANSI A117.1.

1.6 DELIVERY, STORAGE, AND HANDLING

A. Deliver products to site under provisions of Section 01 60 00.
B. Store and protect products under provisions of Section 01 60 00.

C. Package signs, labeled in name groups.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

A. Acceptable Manufacturers:
1. Seton Identification Products.
2. Corpus Christi Stamp Works.
3. Allenite 755 System.
4. Andco PME 1000 Series.
5. ASI Intouch System.
6. Bestsigns HC300 ADA System.

B. Requests for substitutions will be considered in accordance with provisions of Section 01 60 00.

2.2 MANUFACTURED UNITS

A. Room Name/Number Signage:
1. Colors: Selected by Architect from manufacturer's full range of available colors & styles.
2. Sign Size: 8 inches (203 mm) wide by 4 inches (102 mm) high.
3. Lettering: 5/8 inch (16 mm) high, raised 1/32 inch (0.8 mm) with domed grade 2 braille. Letter style shall be San Serif.

B. Directional Signage:
1. Colors: Selected by Architect from manufacturer's full range of available colors & styles.
2. Sign Size: 9 inches (229 mm) wide by 9 inches (229 mm) high.
3. Graphics: International symbol of accessibility for indicated information, with directional arrows.
4. Lettering: 5/8 inch (16 mm) high, raised 1/32 inch (0.8 mm), with domed grade 2 braille. Letter style shall be San Serif.

C. Restroom & Fire Exit Signage:
1. Selected by Architect from manufacturer's full range of available colors & styles.
2. Sign Size: 6 inches (152 mm) wide by 9 inches (229 mm) high.
3. Graphics: International symbol of accessibility for indicated information.
4. Lettering: 5/8 inch (16 mm) high, raised 1/32 inch (0.8 mm), with domed grade 2 braille. Letter style shall be San Serif.

D. Accessories: Installation accessories specified in manufacturer's instructions.

PART 3 - EXECUTION

3.1 EXAMINATION

A. Verify that surfaces to receive signs have been finished, and that finishes are dry and correctly cured.

3.2 INSTALLATION

A. Install room and door signs in accordance with manufacturer's printed installation instructions.

B. Locate signs in accordance with approved shop drawings and ADA requirements.

END OF SECTION 101467